

### **About HIC Transmission Rubber Belts**


ISO 9001 certified HIC International, 1988 formed company, Delhi based Indian producer of Speedy-Power Machine Run, Extreme Strength, Mechanical Power Transmission Drive Belting, exporting to industries in Asia, Europe, Africa, Oceania, America to customer's thorough satisfaction.

Full-proof Quality Assurance Plan details on: www.UniversalDelhi.org

Credentials of Quality World-wide Supplies details on: www.Rubber-Steel-Industrial-Products.com

Range of Tailor-made Power-drive Rotation Manufacturing details on: www.hicRubber.com

## EXTREME STRENGTH



Cotton Hard Duck Rubber as per IS 1370



Leather Nylon per ISO 554



Balata Packing as per BS 351



Nylon per ISO R284



Vendor Data for Supplier Enlistment information on: www.hicPowerDrive.com

















# Why Choose HIC UNIVERSAL Flat Belting?

#### Energy Efficient Nylon Core Leather Fabric LF, LL, TA, TFO

Reduces Power Consumption in Textile, Paper Machines, Marble Gangsaw Shaft Rotation



**High Breaking Strength** Cotton Duck Plies 37oz., 34oz, 31oz Ensures High Speed in Rice & Flour Processing, Agri. Water Pump



High Friction Surface Rubber Flat Belting XRS, AR

Allows Extreme Power Transmission in Package Handling, Parcels

#### **MANUFACTURING RANGE:**

Nylon Leather/Rubber Nylon/Tangential, up to 7.5 mm Thick & 0.7 m W, as per IS 6538 Rubber Cotton 37oz/34/31/28oz, 3~12 Ply & 1.05 m W, as per IS 1370 Leather Nylon core, up to 8 mm Thick & 300 mm W, as per ISO 4184



Technical Specifications download from: www.hic-india.com

RFQ rubber flat belt, leather belting specs. As stated below, in English language please, to quote price offer:

- 1. Width of flat transmission belting, MM
- 2. Thickness or Ply
- 3. Type and Grade
- 4. Color
- Quantity- Open Ends roll length in Meter or Endless loop length

